

## AMENDMENTS TO THE CLAIMS:

Replace the claims with the following rewritten listing:

1. (Currently Amended) Electroluminescent (EL) lamp driver for controlling the luminescent brightness of at least two EL lamps ~~(28, 38)~~, comprising  
means for receiving at least two luminescent brightness setpoint values for said respective EL lamps and at least one charging means, ~~characterized by and~~  
control means for setting the luminescent brightness of the EL lamp with ~~the~~ a highest luminescent brightness setpoint by controlling an output parameter of the charging means ~~(10)~~, and for setting the luminescent brightness of an EL lamp or the EL lamps with a lower luminescent brightness setpoint by controlling a time interval during which this EL lamp or these EL lamps is/are charged in parallel to the first EL lamp.
2. (Currently Amended) EL lamp driver according to claim 1, wherein said control means comprises means for generating charge waveforms ~~(128, 138)~~ in accordance with the received setpoint values for charging or discharging the EL lamps ~~(28, 38)~~.
3. (Currently Amended) EL lamp driver according to claim 1 ~~or 2~~, wherein said control means comprises means for generating a first charge waveform ~~(128)~~ for charging a first one of the EL lamps ~~(28 or 38)~~ with the highest desired luminescent brightness and a second charge waveform for charging a second EL lamp ~~(38 or 28)~~ with lower desired luminescent brightness.
4. (Currently Amended) EL lamp driver according to claim 3, wherein the first charge waveform ~~(128)~~ fully charges the first one of the EL lamps ~~(28 or 38)~~ with the highest desired luminescent brightness and the second charge waveform has essentially the same waveform ~~(138)~~ as the first charge waveform ~~(128)~~ during a time interval which is smaller than ~~the~~ a time interval during which the first one of the EL lamps is charged.

5. (Currently Amended) EL lamp driver according to ~~any one of claims 1 to 4~~claim 1, wherein said control means~~(40; 50, 55, 56, 60, 65, 66, 70-79, 91-94)~~ is adapted to receive on its inputs the luminescent brightness setpoint values ~~(41, 42)~~ for at least two EL lamps ~~(28, 38)~~ and actual values ~~(84, 85)~~ corresponding to the an actual luminescent brightness of the at least two EL lamps ~~(28, 38)~~, to compare the respective setpoint value and actual value for each of the at least two lamps, and to drive charging means~~(10)~~, discharging means~~(12)~~, and H-bridges ~~(20-23, 30-33)~~ for the EL lamps ~~(28, 38)~~ in such a way that the setpoint value and the actual value for each of the at least two EL lamps ~~(28, 38)~~ are substantially equal.
  
6. (Currently Amended) EL lamp driver according to ~~any one of claims 1 to 5~~claim 1, wherein said control means comprises a controller ~~(50, 60)~~ for each of the at least two EL lamps ~~(28, 38)~~, wherein each controller ~~(50, 60)~~ receives on its inputs ~~(57, 58, 67, 68)~~ the setpoint value and ~~the~~ an actual value of a corresponding one of the at least two EL lamps ~~(28, 38)~~ and is adapted to generate a control signal ~~(59, 69)~~ on its output for controlling the charging and discharging means ~~(10, 12)~~ or a pulse-width modulator ~~(72)~~ for generating a control signal ~~(83)~~ for controlling the charging or discharging of the EL lamp or lamps with the lower luminescent brightness setpoint or setpoints.
  
7. (Currently Amended) EL lamp driver according to ~~any one of claims 1 to 6~~claim 1, wherein the charging means ~~(10)~~ comprise a high voltage power supply which is able to source for causing a current to flow into the EL lamps ~~(28, 38)~~.
  
8. (Currently Amended) EL lamp driver according to claim 7, wherein the power supply is a step-up switching power supply with a control input for setting ~~the a~~ duty cycle on ~~the a~~ primary side switching.
  
9. (Currently Amended) EL lamp driver according to ~~any one of claims 1 to 8~~claim 1, wherein the discharging means ~~(12)~~ comprise a control input for determining ~~the an~~ amount of sink current out of the EL lamps.

10. (Currently Amended) EL lamp driver according to claim 9, wherein the discharging means ~~(12)~~ comprises a resistor, a current sink based on a transistor, or a step-down switching power supply with a charge storage device on the primary side for absorbing energy removed from the EL lamp or lamps.
11. (Currently Amended) EL lamp driver according to ~~any one of the preceding claims~~ claim 1, wherein said output parameter comprises an output voltage and/or an output current of said charging device
12. (New) EL lamp driver according to claim 2, wherein said control means comprises means for generating a first charge waveform for charging a first one of the EL lamps with the highest desired luminescent brightness and a second charge waveform for charging a second EL lamp with lower desired luminescent brightness.
13. (New) EL lamp driver according to claim 12, wherein the first charge waveform fully charges the first one of the EL lamps with the highest desired luminescent brightness and the second charge waveform has essentially the same waveform as the first charge waveform during a time interval which is smaller than the time interval during which the first one of the EL lamps is charged.